

This guide specification is provided in CSI Format, for use by design and construction professionals. The patented design of DryFlekt Kick-Out Flashing creates a downward, outward flow of water away from walls, preventing water intrusion at the roof/eave intersection. Please contact us at the number above for assistance.

SECTION 07645 (076600)

PREFORMED ROOF FLASHINGS

PART 1 - GENERAL

1.01 SUMMARY

- A. Provide preformed kick-out flashing at eave of sloped roofing adjacent to vertical walls.

1.02 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions.

1.03 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products which have been in satisfactory use in similar service for two years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.

PART 2 - PRODUCTS

2.01 MATERIALS

- A. Preformed Roof Flashing: DryFlekt Kick-Out Diverter Flashing as manufactured for DryFlekt Products Inc., 128 Radio Circle Drive, Mount Kisco, NY 10549; toll free (877) 985-1010; fax (877) 985-1011, info@dryflekt.com, www.dryflekt.com.
 - 1. Material: UV-resistant, non-corrosive polypropylene copolymers.
 - 2. Thickness: 1/16 inch.
 - 3. Color: [Brown] [Grey] [Tan] [White] [Bronze] [Sand].

PART 3 - EXECUTION

3.01 INSTALLATION

- A. Install materials in accordance with manufacturer's instructions and in proper relationship with adjacent construction. Coordinate sequence of construction with installation of adjacent materials.
- B. Clean and protect work from damage.

END OF SECTION